

Таблица соответствия спиральных зажимов

			Диаметр кабеля																		
			6,6–7,6	7,6–8,3	8,4–9,1	9,5–10,5	10,6–11,6	11,7–12,8	12,9–14,1	14,2–15,6	15,7–17,3	17,4–19,1	19,2–20,9								
Зажим натяжной спиральный	без протектора	для ОКСН	AND	AND-1,5(3)			AND-2(3,5)			AND-3(5)				AND-5(9)		AND-6(10)		AND-9(15)			
				ANZ-7(12)			ANZ-10(17)			ANZ-15(25)			ANZ-20(35)		ANZ-25(40)		ANZ-30(50)		ANZ-60(100)		
				ONZ										ONZ-30...240							
				AX										AX-50							
				AXR									AXR-110								
				SL									SL-500				SL-800				
				AXC									AXC-500				AXC-800				
	с протектором	для грозотроса	SLO							SLO-500				SLO-800							
	Зажим поддерживающий спиральный	без протектора	для ОКСН	AX	AX-50																
					AXR									AXR-110							
					SL									SL-500				SL-800			
					AXC									AXC-500				AXC-800			
с протектором		для грозотроса	SLO							SLO-500				SLO-800							

Возможно изготовление любых типоразмеров.